TRANSPOWER® SWITCHGEAR INDUSTRIES

E-mail : transp@mtnl.net.in / transp@vanl.com • www.transpowerindia.com Tel. : (0) 2512 5237 / 2510 7952 • Fax : 2502 2170 Mob. : 9820539902 / 9820351340 / 9920539902

WATER CO, TYPE FIRE EXTINGUISHER

Suitable for A class of fire involving carbonaceous materials such as Paper, Wood, Clothes, Plastics etc.

| Extinguishing agent | Water Cooling | | |
|-----------------------------|---------------|----------|----------|
| Available capacity in Itrs. | 9 | 50 | 150 |
| IS Specification | 940 | 13385 | 13385 |
| Jet range in mtrs. | 6 | 10 | 20 |
| Discharge time in secs. | 60 - 120 | 60 - 180 | 60 - 180 |



MECHANICAL FOAM (AFFF) TYPE FIRE EXTINGUISHER

Suitable for A & B class of fire involving Paper, Wood, Clothes, Plastics etc. Petrol, Oil, Paints, Thinner, Spirits etc.

| Extinguishing agent | Foam Blanketing | | |
|-----------------------------|-----------------|----------|----------|
| Available capacity in Itrs. | 9 | 50 | 150 |
| IS Specification | 10204 | 13386 | 13386 |
| Jet range in mtrs. | 6 | 10 | 16 |
| Discharge time in secs. | 25 - 90 | 60 - 180 | 60 - 180 |



DRY POWDER TYPE FIRE EXTINGUISHER

Suitable for B & C class of fire involving Petrol, Oil, Paints, Thinner, Spirits, Flammable Gases & Electrical fires etc.

| Extinguishing agent | Dry Powder Blanketing | | | | | | |
|-------------------------|-----------------------|-------|-------|--------------------------|-------|-------|--|
| Available cap. in kgs. | 1, 2 | 5 | 10 | 25 | 50 | 75 | |
| IS Specification | 2171 | | | Specification 2171 10658 | | | |
| Jet range in mtrs. | 2 | 4.5 | 6 | 6 | 8 | 10 | |
| Discharge time in secs. | 8-10 | 15-20 | 23-30 | 25-30 | 40-50 | 50-60 | |



CO, TYPE FIRE EXTINGUISHER

Suitable for B & C class of fire involving Petrol, Oil, Paints, Thinner, Spirits, Flammable Gases & Electrical

| Extinguishing agent | CO ₂ Gas Blanketing | | | | | |
|----------------------------|--------------------------------|-------|-------|-------|-------|-------|
| Available capacity in kgs. | 1, 2 | 3 | 4.5 | 6.5 | 9 | 22.5 |
| IS Specification | | | 2878 | MIL | in s | |
| Jet range in mtrs. | 2 | 2 | 2-5 | 2.5-3 | 2.5-3 | 2.5-3 |
| Discharge time in secs. | 14-16 | 16-18 | 20-24 | 25-30 | 25-35 | 50-60 |



ABC DRY POWDER TYPE FIRE EXTINGUISHER

Suitable for A, B & C class of fire involving Paper, Wood, Clothes, Plastics etc. Petrol, Oil, Paints, Thinner, Spirits etc. Flammable Gases, Electrical fires etc.

| Extinguishing agent | Dry Powder Blanketing | | |
|----------------------------|-----------------------|-------|-------|
| Available capacity in kgs. | 1, 2 | 5 | 10 |
| IS Specification | 13849 | | |
| Jet range in mtrs. | 4 | 4 | 4 |
| Discharge time in secs. | 8-10 | 15-20 | 20-30 |



ABC MODULAR TYPE AUTOMATIC FIRE EXTINGUISHER

Suitable for A, B & C class of fire involving Paper, Wood, Clothes, Plastics etc. Petrol, Oil, Paints, Thinner, Spirits etc. Flammable Gases, Electrical fires etc.

| Extinguishing agent | Dry Powder Blanketin | | |
|----------------------------|----------------------|----|----|
| Available capacity in kgs. | 5 | 10 | 15 |
| Discharge time in secs. | 3 | 5 | 8 |



CO2 GAS CARTRIDGES

FOR USE IN FIRE EXTINGUISHERS

Available Capacity 30 / 60 / 120 / 200 / 300 / 500 Gms.

